

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

2
4
6
8
10
Claim 1. (currently amended): An attachment for a putter head ~~capable of being~~
shaped and sized to be attached thereto by any suitable means; said attachment
~~having comprising~~ an attachment location and ~~at least one arcuate face or edge~~
or ~~more further planar~~ faces or edges defining at least one recess therebetween;
said recess being defined behind, in front of, or above the putter head in terms
of the conventional striking direction; wherein at least one recess is adapted to
receive an object or article such as a conventional receives a golf ball and
restricts the movement thereof in a direction parallel to the a striking face of a
putter head when the ~~said~~ golf ball is in contact with the ~~said~~ one or more faces
or edges during the swinging of the putter by a user.

Claim 2. (cancelled).

2
Claim 3. (currently amended): An attachment according to claim 1 wherein said
attachment is ~~adapted to be~~ disposed behind the a striking face of the putter head

according to the direction in which a ball would be conventionally struck
thereby during use.

Claim 4. (currently amended): An attachment according to claim 1 wherein the
attachment is provided with at least one arcuate hoop behind or in front of the
attachment location, the edges or faces defining same having a separation which
is marginally greater than that of the diameter of the conventional a golf ball.

Claim 5. (currently amended): An attachment according to claim 1 wherein the
attachment is provided with a pair of spaced limbs extending substantially
parallel rearwardly or forwardly of the attachment location and generally
perpendicular to the a striking face of said putter head, the separation of said
limbs being marginally greater than the diameter of a conventional golf ball.

Claim 6. (currently amended): An attachment according to claim 1 wherein the
means for attachment of said attachment ~~ensures~~ provides uniform and
repeatable attachment to the ~~said~~ putter head.

Claim 7. (new): An device comprising an attachment face shaped and sized for
attachment to a club head of a putter and one or more receiving faces defining
by themselves or in combination with a surface of said club head at least one

4 orifice for receiving a golf ball and restricting the movement of said golf ball
during a portion of a swing of the putter by a user.

Claim 8. (new): A device according to claim 1 wherein said device is attachment
2 face is disposed behind said orifice.

Claim 9. (new): A device according to claim 1 wherein said device is attachment
2 face is disposed in front of said orifice.

Claim 10. (new): A device according to claim 1 wherein the device comprises at
2 least one hoop behind or in front of the attachment face and sized to receive a
golf ball.

Claim 11. (new): A device according to claim 1 wherein the attachment is provided
2 with a pair of spaced limbs extending away from the attachment face, the
separation of said limbs being marginally greater than the diameter of a golf
4 ball.

Claim 12. (new): A device according to claim 1 further comprising a means for
2 uniform and repeatable attachment to a putter head.